

- Full Metal Housing with durable powder spray coating.
- Unique Arc desing and slim body.
- High efficiency.
- Low noise.
- Convenient operation.
- Easily adjust air pattern.
- Available in: 900, 1200 and 1500 mm.



FM / 115V

Model		FM-1209N-2Y-220	FM-1212N-2Y-220	FM-1215N-2Y-220
Voltage	(V/Ph/Hz)	115/1/60	115/1/60	115/1/60
Max. Wind Speed	(m/s)	11	11	11
Air Flow	CFM	1,200	1,700	2,100
Noise Level	dB	≤ 58	≤ 59	≤ 59
Max. Input Power	W	150	180	220
Diameter of Wheel	in	4.72	4.72	4.72
Installation Height	ft	7.5-9.8	7.5-9.8	7.5-9.8
Net weight	lbs	28.66	28.66	28.66
Dimensions Air Curtain	in	35.4x8.6x7.7	47.2x8.6x7.7	59.1x8.6x7.7
Packing Dimensions	in	37.8x11.0x9.8	49.6x11.0x9.8	62.4x11.0x9.8

FM / 220V

Model		FM-1209N-2Y-220	FM-1212N-2Y-220	FM-1215N-2Y-220
Voltage	(V/Ph/Hz)	230/1/60	230/1/60	230/1/60
Max. Wind Speed	(m/s)	11	11	11
Air Flow	CFM	1,200	1,700	2,100
Noise Level	dB	≤ 58	≤ 59	≤ 59
Max. Input Power	W	150	180	220
Diameter of Wheel	in	4.72	4.72	4.72
Installation Height	ft	7.5-9.8	7.5-9.8	7.5-9.8
Net weight	lbs	28.66	28.66	28.66
Dimensions Air Curtain	in	35.4x8.6x7.7	47.2x8.6x7.7	59.1x8.6x7.7
Packing Dimensions	in	37.8x11.0x9.8	49.6x11.0x9.8	62.4x11.0x9.8



- 1.- All dimensions and performance rates could change, please contact ECOX for the latest information available.
- 2.- The values reflected in the level of noise were made in an anechoic chamber.

