



SEER 10



Auto Restart



Washable Filters



Turbo Mode



Less Vibration



Less Noise



Multiposition (Horizontal/ Vertical)

- Available in 18.000, 24.000, 36.000, 48.000 and 60.000 BTU
- Refrigerant R22

60Hz

R-22





SEER¹⁰

R-22



LOW NOISE



MULTI POSITION
(HORIZONTAL / VERTICAL)



AUTO RESTART



LESS
VIBRATION



WASHABLE
FILTERS

Model		NAHU018C10B	NAHU024C10B	NAHU036C10B	NAHU048C10B	NAHU060C10B
Power Supply	V / Ph / Hz	220V~230V/1 PH/60Hz	220V~230V/1 PH/60Hz	220V~230V/1 PH/60Hz	220V~230V/1 PH/60Hz	220V~230V/1 PH/60Hz
Rated Cooling Capacity	Btu/h	18.000	24.000	36.000	48.000	60.000
EER Cooling		2,82	2,78	2,62	2,78	2,32
Max. input consumption	Watts	1879	2554	4008	5036	6820
Noise level (Indoor)	dB(A)	49	49	50	51	52
INDOOR FAN MOTOR						
Output	Watts	267/218	267/218	461/325	500/420	660/512
Capacitor	uF	6UF/450V	6UF/450V	10uF/450V	12uF/450V	12uF/450V
FAN Speed	RPM	635/530	635/530	925/730	800/720	985/760
Indoor air flow	m3/h	840	840	1130	1355	1590
Dimension(WxDxH)	mm	18 1/8" x 20 1/2" x 39 3/8"	18 1/8" x 20 1/2" x 39 3/8"	18 1/8" x 20 1/2" x 39 3/8"	21 1/4" x 20 1/2" x 47 1/4"	21 1/4" x 20 1/2" x 47 1/4"
Packing (WxDxH)	mm	20 1/2" x 22 7/8" x 41 3/4"	20 1/2" x 22 7/8" x 41 3/4"	20 1/2" x 22 7/8" x 41 3/4"	23 5/8" x 22 7/8" x 49 5/8"	23 5/8" x 22 7/8" x 49 5/8"
Net/Gross weight	Kg	103 / 113	103 / 113	113 / 123	139 / 150	112/121
OTHER						
Line Set Gas	in	1/4"	3/8"	3/8"	3/8"	3/8"
Line Set Liquid	in	1/2"	5/8"	3/4"	3/4"	3/4"
Refrigerant		R22	R22	R22	R22	R22
Design Pressure	Mpa	2.6/1.0	2.6/1.0	2.6/1.0	2.6/1.0	2.6/1.0
Drainage water pipe diameter	in OD	3/4"	3/4"	3/4"	3/4"	3/4"



*The wire gauge is factory recommended, please refer to the appropriate local code to select the wire size.
*All dimensions and performance rates could change.

